

Specifications

Mechanics

Table travel X, Y, Z

Work area: x= 100 mm y=125 mm optional
Resolution 0, 25 µm, repeatability < 2 µm

Speed

All axes programmable from 0.2 to 6 mm/s
Test speed from 0.2 to 5mm/s

Measurement heads

Accuracy

0.25 % of max value

Calibration

Stored in measurement head; temperature-compensated
load cell
Optional calibration at customers side (specific tools)

Control

Computer

Single-Board PC, 1 GHz Pentium processor, 1 GB RAM,
Ethernet, USB 4x frontside

Monitor

TFT flat screen monitor Min. 17"

Operating system

Windows XP

Printer

all Windows-compatible printers can be installed



Additional features

Programming

Automatic repeat measurements on hybrids or COB using
the programmable table movement and Pattern Recognition
Unit (PRU)

Evaluation

Statistics such as mean value, standard deviation, trend, cp,
cpk, etc. Based on SQL Databank

5600C

Automatic Bond Tester

The automatic bond tester 5600 complements F&K Delvotec Semiconductor GmbH die- and wire- bonders.

The PC controlled moving table allows any number of bonds to be tested automatically from a stored program.

Results can be analysed and output immediately or exported in a number of data base formats for subsequent analysis as desired.

Powerful extended capabilities enable measurements such as force/time or force/distance curves to be made and deliver more data about the quality of the bond tested.

Exchangeable measurement cartridges ensure rapid conversion to different force ranges. The calibration curves of all measurement cartridges are stored internally; additional heads for shear, peel and tweezer testing with customer-specific tools and jaws are available.

After a first programming a reproducible pull- or sheartest can be guaranteed for all following components.

F&K Delvotec Semiconductor GmbH
Industriezeile 49a
A-5280 Braunau am Inn, Austria
Tel.: +43-7722-67052-8270,
Fax: +43-7722-67052-8272
Email: info@fkdelvotec.at
Internet: www.fkdelvotec.at

F&K Delvotec Bondtechnik
GmbH & Co.KG
3 International Business Park
#04-05 Nordic European Centre
Singapore 609927
Tel. +65-6890-6020, Fax +65-6890-6021

F&K Delvotec, Inc.
27182 Burbank Ave,
Foothill Ranch, CA 92610 USA
Tel. +1-949-595-2200, Fax +1-949-595-2207

<i>Export format</i>	SQL, CSV, HTML
<i>Other</i>	Operator profile, various password levels, optional barcode readers for product identification; feedback of measured values to die and wire bonders for parameter optimisation optional
<i>P2B option</i>	Communication with F&K Delvotec die- or wire-bonder
Test-Cartridge	

Pulltester Cartridge



Available Pullheads:
PH100C 100 cN
PH1000C 1000 cN
PH5000C 5000 cN

Sheartester Cartridge



Available Shearheads:
SH500C 5000 cN
SH5000C 50000 cN

Tweezertester Cartridge



Available Tweezerhead
TH100C 100 cN

The Test-Cartridges can be changed without any tool within less than 1 minute

General

Microscope

Lighting

Dimensions

Supplies

Connections

Stereoscope Motic SMZ, other microscopes optional

20 W halogen spot light (optionally LED ring light)

Height 70 cm, width 70 cm, depth 65 cm;
weight approx. 80 kg

100...240 VAC, single phase, 50/60 Hz, max. 500 VA

Air 6 bar; vacuum 0, 7 bar

F&K Delvotec Semiconductor GmbH
Industriezeile 49a
A-5280 Braunau am Inn, Austria
Tel.: +43-7722-67052-8270,
Fax: +43-7722-67052-8272
Email: info@fkdelvotec.at
Internet: www.fkdelvotec.at

F&K Delvotec Bondtechnik
GmbH & Co.KG
3 International Business Park
#04-05 Nordic European Centre
Singapore 609927
Tel. +65-6890-6020, Fax +65-6890-6021

F&K Delvotec, Inc.
27182 Burbank Ave,
Foothill Ranch, CA 92610 USA
Tel. +1-949-595-2200, Fax +1-949-595-2207